



Thanks for choosing **aeroe**

We hope that this is the start of a long and happy relationship that will enable you to use your bike more often, for more adventures in an easier and more enjoyable way.

If you're like us and tend to skip the instructions and just start putting it together. . . . . we understand. However if you would like some help getting set up, below are some important and handy tips and tricks for installing your aeroe gear.

All you need to install any of our products is a standard 5mm allen key. Take a moment to familiarise yourself with some of the jargon below shown on the **spider pannier rack**. The following steps will then allow you to get setup quickly and easily so you can get out and start enjoying your new gear!



Tool required for install - **5mm allen key**

We love seeing and hearing about your adventures around the world. . . . . if you want to reach out or still need installation help - we would love to hear from you! You can reach us at [team@aeroe.com](mailto:team@aeroe.com) or on facebook and instagram [#aeroebikepack](https://www.instagram.com/aeroebikepack) or check out [aeroe.com](http://aeroe.com) for more information.

Thanks again from the aeroe team!

start here

1



Start by unscrewing the bolts that loosen the **4 straps** with allen key (see step 2 for bolt location). If you are using on a carbon frame we recommend a layer of standard bike tape or mastic tape on area of seat stays prior to install. Once the straps are loose, position the **straps** on your seat stays and connect the hole in the strap with the lug in the **feet**. Note the 2 holes in the straps. Choose the hole that best suits the thickness of your stays. Once the **feet** are roughly in place, start tightening the **straps** using the allen key in the 4 bolts as shown in the next step.

2



We suggest tightening **2 straps** on one side of the bike first to about 75% tight, to form some stability and then making sure the rack is positioned upright and even on both sides and then tightening the **straps** on the other side to 75%. Adjust as required. Once the rack looks like its in the right place. Tighten **straps** to 100%. Max tightening of 4Nm torque. We normally suggest this works out to be tightened to a firm hand tighten with the allen key is about right, but you can use a torque tool to measure this if required.

3



Depending on the size of your bike or seat, you can loosen the bolts shown above and slide the **spider pannier rack** down to suit preferred height, and then tighten the bolts again. If you loosen these bolts the **feet** can be rotated also to help with fitting if you have angled seat stay as shown in the next step if required.

**HOT TIPS** If you loosen the bolts above you can also rotate the whole **spider pannier rack** 180 degrees if you want your gear to sit further back from your seat.


4



By now your rack should be securely installed and look something like this, and ready to have the cradle/s installed.

**HOT TIPS** Your rack should fit if installed as per above, however if you have a bespoke or narrow frame, here's a couple of hot tips to help. **1.** Loosen the 4 bolts shown in step 5 and you can rotate the **feet** to fit the angle of your seat stays. **2.** The **spider pannier rack** has been designed to be flexible. The legs of the rack can be pressed together with force required to suit the width of your seat stays up to 20mm in and out each side if required.

5



Installing the **spider pannier receiver** is easy. The spider pannier receiver mounts on the top of the **spider pannier rack** or your existing **spider rear rack**. Simply unscrew the 4 screws within the pannier receiver with a 5mm allen key, locate the male and female part of the pannier receiver on the **spider pannier rack** or **spider rear rack**.

Tighten to 80%. Ensure **pannier receiver** is level and tighten to 100%.

6



To install the lower pannier catch **anti-sway fingers**, loosen the **anti-sway finger** bolt so you can pull the clamp of the **anti-sway finger** apart enough to slide onto the **spider pannier rack**.

With the bolts slightly loosened, Slide the **anti-sway finger** up the rack into the correct position and adjust the position of the finger to suit your pannier. Tighten to 100% once in the right position.

Now that your rack is installed, hook your panniers over the pannier receiver and connect to the anti-sway fingers below and enjoy!  
**Thanks again from the aero team!**